
## **HOLLOW CORE SLAB 25 CM.**



## SECTION PROPERTIES

TOPPING	0 CM.	5 CM.					
A (cm. <sup>2</sup> )	1,385	-					
l (cm. <sup>4</sup> )	104,761	183,295					
Y <sub>b</sub> (cm.)	12.58	16.33					
Y <sub>t</sub> (cm.)	12.42	13.67					
$Z_b$ (cm. <sup>3</sup> )	8,327	11,222					
$Z_t$ (cm. <sup>3</sup> )	8,435	13,409					
w (kg/m.²)	277	419					
e (cm.)	9.58	13.33					
b <sub>w</sub> (cm.)	37						

	SAFE SUPERIMPOSED SERVICE LOADS (KGS/SQ.M)																	
No. of Ø Mn			_	SIMPLE SPAN IN METER														
TOPPIN	G STRAND (kg-m.)		4	4.5	5	5.5	6	6.5	7	7.5	8	8.5	9	9.5	10	10.5	11	11.5
	4-Ø 3/8"	7,865.54	1,695	1,290	1,001	787	624	497	396	315	249	194	148					
	5-Ø 3/8"	9,727.47	2,156	1,655	1,297	1,032	831	674	550	450	367	299	242	194	153			
	6-Ø 3/8"	11,548.96	2,602	2,008	1,583	1,269	1,029	843	696	577	479	398	331	273	224	182		
	7-Ø 3/8"	13,330.68	3,039	2,353	1,862	1,500	1,224	1,009	839	701	588	495	417	351	294	246	203	167
0 cm.	8-Ø 3/8"	15,073.27	3,466	2,690	2,136	1,725	1,413	1,170	978	822	695	590	501	426	362	308	260	218
	9-Ø 3/8"	16,777.38	3,466	2,887	2,403	1,946	1,599	1,329	1,114	941	799	682	584	500	428	363	306	256
	10-Ø 3/8"	18,443.66	3,466	2,887	2,556	2,162	1,780	1,483	1,247	1,057	902	772	664	570	487	416	355	301
	2-Ø 1/2" +8-Ø 3/8"	21,032.46	3,466	2,887	2,556	2,408	1,987	1,724	1,455	1,238	1,060	911	783	674	581	502	432	372
	4-Ø 1/2" +6-Ø 3/8"	23,528.57	3,466	2,887	2,556	2,408	1,987	1,879	1,625	1,380	1,183	1,015	880	764	662	574	497	430
	4-Ø 3/8"	9,495.46	1,977	1,489	1,139	881	684	531	410	312	232	165						
	5-Ø 3/8"	11,712.20	2,517	1,915	1,485	1,166	924	736	591	471	372	290	221	163				
	6-Ø 3/8"	13,852.33	3,041	2,326	1,825	1,449	1,162	939	762	620	503	406	325	256	182			
5 cm.	7-Ø 3/8"	15,928.49	3,554	2,736	2,150	1,717	1,388	1,132	928	764	630	518	425	346	267	190		
	8-Ø 3/8"	17,942.13	4,046	3,124	2,466	1,978	1,607	1,318	1,089	904	753	628	523	434	352	267	193	
	9-Ø 3/8"	19,894.65	4,046	3,368	2,772	2,231	1,819	1,499	1,245	1,040	872	733	609	489	386	298	221	154
	10-Ø 3/8"	21,787.47	4,046	3,368	2,959	2,476	2,025	1,675	1,396	1,172	988	836	707	577	466	370	287	214
	2-Ø 1/2" +8-Ø 3/8"	24,695.09	4,046	3,368	2,959	2,761	2,265	1,935	1,629	1,365	1,156	983	839	700	575	465	374	292
	4-Ø 1/2" +6-Ø 3/8"	27,458.93	4,046	3,368	2,959	2,761	2,558	2,127	1,840	1,555	1,324	1,132	971	835	701	581	478	388